

### Features :

- **Copper base , Stainless steel Rain-gun**
- **Distributes water consistently**
- Speed Adjustable
- Atomization can be adjusted
- 24° Elevation
- Rotation angle: 0-360° (Controlled)
- **2" Copper Female thread Connect or 6-hole flange is optional**

### Operating Specifications

- Flow rate 10-70 m<sup>3</sup>/h
- Working pressure: 0.2 – 0.7 MPa
- Spray range: 23-56 m
- Style: Flange style with 43° high elevation lengthened type
- Nozzle Size: 6 from 14 to 30

**Model Size : XT-RG2" / XT-RG3"**

Noz dia	Working	Flow rate	Jet length
mm	kg/cm <sup>2</sup>	m <sup>3</sup> /h	m
20	3	17.5	31
	4	19.9	34
	5	22.8	36
	6	24.7	39
	7	26.6	41
	8	28.5	42
22	3	31.9	33
	4	25.5	36
	5	28.2	39
	6	30.9	41
	7	33.2	43
	8	35.8	45
24	3	25.8	35
	4	32.3	39
	5	35	41
	6	38.5	44
	7	41.5	46
	8	44.5	48
26	3	33.5	38
	4	37.5	41
	5	42.5	44
	6	46.5	46
	7	49.8	48
	8	53.2	50
28	3	39.2	40
	4	45.3	43.6
	5	50.3	46
	6	54.6	48
	7	58.5	51.5
	8	63.3	53
30	3	60.2	47
	4	71.5	51
	5	78.3	53
	6	85.5	54
	7	92.8	56.3
	8	98.9	58.8

