

Features :

- XT Dripline – Blank with greater flexibility is easier to install and saves time
- Brown color matches landscape and blends with mulch.
- Matches XT Series Dripline
- Accepts and compatible with Xeritech XT Dripline Insert Fittings, and 17mm insert fittings

Operating Range

- Pressure: 8.5 to 60 psi (0.58 to 4.14 bar)
- Temperature: Up to 100° F (43.3 C) water; up to 125 F (51.7° C) ambient
- Required filtration: 120 mesh / 125 Micron

Features:

- Application : On Surface
- Emitter Spacing : Blank Tubing / No Emitters
- Tubing Diameter : 1/2 in with 1.2mm wall thickness

Specification

- Outside diameter : 0.634" (16.1 mm)
- Inside diameter : 0.536" (13.6 mm)
- Thickness(Wall) : 0.049" (1.2 mm)
- Spacing : NA
- Length : 400 Mtrs / Roll



Models :

XTBLANK 1.2mm wall thickness- Blank Brown Lateral

Features :

- Easy Installation and fast due to Extra flexibility tubing
- Dual-Lay layered tubing (brown over black) provides unmatched resistance to chemicals, UV damage and algae growth.
- Increase reliability due to patent pending emitter design

Operating Range

- Pressure: 8.5 to 60 psi (0.58 to 4.14 bar)
- Temperature: Up to 100° F (43.3 C) water; up to 125 F (51.7° C) ambient
- Required filtration: 120 mesh / 125 Micron

Specification

Used with XT Dripline Insert fittings

Outside diameter : 0.634" (16.1 mm)

Inside diameter : 0.536" (13.6 mm)

Thickness(Wall) : 0.049" (1.2 mm)

Spacing : 40 cms / 60 cms

Length : 400 Mtrs / Roll

152 Mtrs / Roll

Models :

XT-INLINE 30cm, 40cm / 60cm spacing

